



Data and communication cable

MarineCom YOZc 250 V

Article number: 16278

24-07-2019

Description14 x 2 x 0,75 mm²**Application:**

Lightweight, armoured, control, instrumentation, tele- and data cable.

Characteristics:

- Twisted pairs, triples or quads
- Perfect electrical properties and low capacitance for minimal signal loss
- Halogen free and low smoke, flame retardant
- Extra mechanical protection and reduced EMI due to the tinned copper braided screen
- Different colour outer sheaths, other than grey, available on request

Core identification:

- Pairs & Quads: Numbered Blue and White . Triples: Numbered Blue, White and Red

**Trading information**

Product group	Data and communication cable
Type	MarineCom YOZc 250 V
Net. Weight	0,481 kg/m
Sheath marking	{Length} TKF-14x2x0,75 - 250V - CS 90 - mbzh - MarineCom YOZc HALOGEN FREE {Batch}

Trade lengths

(16278 / 8713182055622)

Construction characteristics

Certified for shipboard application	Yes
Standardization	IEC 60092-350/-360/-376
Conductor material	Copper



Data and communication cable

MarineCom YOZc 250 V

Article number: 16278

24-07-2019

Conductor surface	Bare
Core lay-up	Concentric layers
Number of conductors per group	2
Diameter conductor	1.11 mm
Nominal cross section conductor	0.75 mm ²
Conductor category	Class 2 = stranded
Number of cores	28
Stranding element	Pairs
Number of stranding elements	14
Core insulation	XLPE (VPE)
Construction outer shield	tinned copper braiding
Binder/filler	Polyester tape
Core identification	Numbers
Overall stranding screen	Braiding
Insulation thickness	0.5 mm
Diameter shield wires	0.3 mm
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound
Colour outer sheath	Grey
Outer diameter approx.	20.2 mm



Data and communication cable

MarineCom YOZc 250 V

Article number: 16278

24-07-2019

Properties

Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1/2
Low smoke	IEC 61034-2
Diameter over braiding	16.8 mm
Nominal outer sheath thickness	1.5 mm
Standardization conductor material	IEC 60228
Standardization sheath material	IEC 60092-360
Tensile load	315 N
Min. bending radius during installation	136 mm
Min. permitted bending radius, stationary application/permanent installation	116 mm

Technical characteristics

Permitted cable outer temperature, in movement	-20 / 70 °C
Permitted cable outer temperature, fixed	-40 / 70 °C
Conductor AC resistance @ max. cont. Conductor temp.	33.2 Ohm/km

Electrical characteristics

Inductance	0.331 mH/km
Conductor DC resistance @ 20°C	26 Ohm/km
Nominal voltage U	250 V
Test voltage	1500 V
Max. conductor temperature	90 °C
Capacity	60 nF/km