



Power cable ≥ 1 kV, for permanent installation

MarineLine YZp 0,6/1 kV

Article number: 16563

24-07-2019

Description

5 x 6 mm²

Application:

Lightweight, unarmoured, reduced diameter low voltage power cables for power and lighting applications in all ship areas.

Characteristics:

- Class 2 conductors
- Lightweight, reduced diameter
- Halogen free and low smoke, flame retardant
- Excellent abrasion resistance
- Different colour outer sheaths, other than black, available on request



Core identification:

- HD308 S2

Trading information

Product group	Power cable ≥ 1 kV, for permanent installation
Type	MarineLine YZp 0,6/1 kV
Net. Weight	0,397 kg/m
Sheath marking	{Length} TKF - 5x6 - 0,6/1 kV - CS 90 - mbzh - MarineLine YZp HALOGEN FREE {Batch}

Trade lengths

	(16563 / 8713182205591)
Reel à 500	(16563H X 500/20 / 8713182205607)



Power cable ≥ 1 kV, for permanent installation

MarineLine YZp 0,6/1 kV

Article number: 16563

24-07-2019

Construction characteristics

Certified for shipboard application	Yes
Standardization	IEC 60092-350/-360/-353
Number of cores	5
Nominal cross section conductor	6 mm ²
Conductor material	Copper
Conductor surface	Bare
Standardization conductor material	IEC 60228
Shape of conductor	Round
Conductor category	Class 2 = stranded
Core insulation	XLPE (VPE)
Core identification	Colours and numbers
	Yes
Protective conductor	No
Core lay-up	Concentric layers
Binder/filler	Polyester tape
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound
Colour outer sheath	Black
Standardization sheath material	IEC 60092-360

Properties

Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1/2
Low smoke	IEC 61034-2
Diameter conductor	3.12 mm
Insulation thickness	0.7 mm
Nominal outer sheath thickness	1.3 mm
Outer diameter approx.	14.7 mm



Power cable ≥ 1 kV, for permanent installation

MarineLine YZp 0,6/1 kV

Article number: 16563

24-07-2019

Technical characteristics

Tensile load	450 N
Min. bending radius after installation	59 mm
Min. bending radius during installation	118 mm
Permitted cable outer temperature, in movement	-20 / 70 °C
Permitted cable outer temperature, fixed	-40 / 70 °C
Max. conductor temperature	90 °C

Electrical characteristics

Nominal voltage U ₀	0.6 kV
Nominal voltage U	1 kV
Test voltage	3500 kV
Conductor DC resistance @ 20°C	3.08 Ohm/km
Conductor AC resistance @ max. cont. Conductor temp.	3.9 Ohm/km
Capacity	51 nF/km
Inductance	0.259 mH/km