



Power cable  $\geq 1$  kV, for permanent installation

## MarineLine YOZp 0,6/1 kV

Article number: 16135

27-08-2019

### Description

3 x 6 mm<sup>2</sup>

### Application:

Lightweight, armoured, reduced diameter low voltage power cables for power and lighting applications in all ship areas.

### Characteristics:

- Class 2 conductors
- Lightweight, reduced diameter
- Halogen free and low smoke, flame retardant
- Tinned copper wire braid armouring
- Excellent abrasion resistance
- Different colour outer sheaths, other than black, available on request



### Core identification:

- HD308 S2

### Trading information

Product group	Power cable $\geq 1$ kV, for permanent installation
Type	MarineLine YOZp 0,6/1 kV
Net. Weight	0,290 kg/m
Sheath marking	{Length} TKF - 3X6 - 0,6/1 kV - CS 90 - mbzh - MarineLine YOZp HALOGEN FREE {Batch}

### Trade lengths

	(16135 / 8713182049348)
Reel à 500	(16135H X 500/20 / 8713182049331)
Reel à 1000	(16135H X 1000/30 / 8713182049355)



Power cable  $\geq 1$  kV, for permanent installation

## MarineLine YOZp 0,6/1 kV

Article number: 16135

27-08-2019

### Construction characteristics

Certified for shipboard application	Yes
Standardization	IEC 60092-350/-360/-353
Number of cores	3
Nominal cross section conductor	6 mm <sup>2</sup>
Conductor material	Copper
Conductor surface	Bare
Standardization conductor material	IEC 60228
Shape of conductor	Round
Conductor category	Class 2 = stranded
Core insulation	XLPE (VPE)
Core identification	Colours and numbers
	Yes
Screening	Yes
Construction outer shield	tinned copper braiding
Core lay-up	Concentric layers
Binder/filler	Polyester tape
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound
Colour outer sheath	Black
Standardization sheath material	IEC 60092-360



Power cable  $\geq 1$  kV, for permanent installation

## MarineLine YOZp 0,6/1 kV

Article number: 16135

27-08-2019

### Properties

Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1/2
Low smoke	IEC 61034-2
Diameter conductor	3.06 mm
Insulation thickness	0.7 mm
Diameter shield wires	0.2 mm
Diameter over braiding	10.2 mm
Nominal outer sheath thickness	1.2 mm
Outer diameter approx.	12.6 mm

### Technical characteristics

Tensile load	270 N
Min. bending radius during installation	88 mm
Min. permitted bending radius, stationary application/permanent installation	50 mm
Permitted cable outer temperature, in movement	-20 / 70 °C
Permitted cable outer temperature, fixed	-40 / 70 °C
Max. conductor temperature	90 °C

### Electrical characteristics

Nominal voltage U <sub>0</sub>	0.6 kV
Nominal voltage U	1 kV
Test voltage	3500 kV
Conductor DC resistance @ 20°C	3.08 Ohm/km
Conductor AC resistance @ max. cont. Conductor temp.	3.9 Ohm/km
Capacity	48 nF/km
Inductance	0.259 mH/km