



Power cable  $\geq 1$  kV, for permanent installation

## MarineLine YOZp 0,6/1 kV

Article number: 16139

27-08-2019

### Description

3 x 10 mm<sup>2</sup>

### Application:

Lightweight, armoured, reduced diameter low voltage power cables for power and lighting applications in all ship areas.

### Characteristics:

- Class 2 conductors
- Lightweight, reduced diameter
- Halogen free and low smoke, flame retardant
- Tinned copper wire braid armouring
- Excellent abrasion resistance
- Different colour outer sheaths, other than black, available on request



### Core identification:

- HD308 S2

### Trading information

Product group	Power cable $\geq 1$ kV, for permanent installation
Type	MarineLine YOZp 0,6/1 kV
Net. Weight	0,464 kg/m
Sheath marking	{Length} TKF - 3X10 - 0,6/1 kV - CS 90 - mbzh - MarineLine YOZp HALOGEN FREE {Batch}

### Trade lengths

	(16139 / 8713182049508)
Reel à 500	(16139H X 500/20 / 8713182049492)
Reel à 1000	(16139H X 1000/30 / 8713182049515)

### Construction characteristics

Certified for shipboard application	Yes
Standardization	IEC 60092-350/-360/-353



Power cable  $\geq 1$  kV, for permanent installation

## MarineLine YOZp 0,6/1 kV

Article number: 16139

27-08-2019

Number of cores	3
Nominal cross section conductor	10 mm <sup>2</sup>
Conductor material	Copper
Conductor surface	Bare
Standardization conductor material	IEC 60228
Shape of conductor	Round
Conductor category	Class 2 = stranded
Core insulation	XLPE (VPE)
Core identification	HD 308 S2
	Yes
Screening	Yes
Construction outer shield	tinned copper braiding
Core lay-up	Concentric layers
Binder/filler	Polyester tape
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound
Colour outer sheath	Black
Standardization sheath material	IEC 60092-360
Ripcord	Yes

### Properties

Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1/2
Low smoke	IEC 61034-2
Diameter conductor	3.85 mm
Insulation thickness	0.7 mm
Diameter shield wires	0.3 mm
Diameter over braiding	12.6 mm
Nominal outer sheath thickness	1.3 mm
Outer diameter approx.	15.2 mm



Power cable  $\geq 1$  kV, for permanent installation

## MarineLine YOZp 0,6/1 kV

Article number: 16139

27-08-2019

### Technical characteristics

Tensile load	450 N
Min. bending radius during installation	106 mm
Min. permitted bending radius, stationary application/permanent installation	61 mm
Permitted cable outer temperature, in movement	-20 / 70 °C
Permitted cable outer temperature, fixed	-40 / 70 °C
Max. conductor temperature	90 °C

### Electrical characteristics

Nominal voltage U <sub>0</sub>	0.6 kV
Nominal voltage U	1 kV
Test voltage	3500 kV
Conductor DC resistance @ 20°C	1.83 Ohm/km
Conductor AC resistance @ max. cont. Conductor temp.	2.3 Ohm/km
Capacity	55 nF/km
Inductance	0.244 mH/km