



Power cable  $\geq 1$  kV, for permanent installation

## MarineFlex YZp 0,6/1 kV

Article number: 16090

21-10-2019

### Description

1 x 35 mm<sup>2</sup>

### Application:

Lightweight, unarmoured, flexible low voltage power cables for power and lighting applications in all ship areas.

### Characteristics:

- Class 5 conductors
- Easy installation in tight spaces due to flexible conductors
- Halogen free and low smoke, flame retardant
- Excellent abrasion resistance
- Different colour outer sheaths, other than black, available on request



### Core identification:

- HD308 S2

### Trading information

Product group	Power cable $\geq 1$ kV, for permanent installation
Type	MarineFlex YZp 0,6/1 kV
Net. Weight	0,359 kg/m
Sheath marking	{Length} TKF - 1X35 Class 5 - 0,6/1 kV - CS 90 - mbzh - MarineFlex YZp HALOGEN FREE {Batch}

### Trade lengths

	(16090 / 8713182051181)
Reel à 500	(16090H X 500/20 / 8713182051174)
Reel à 1000	(16090H X 1000/30 / 8713182051198)



Power cable  $\geq 1$  kV, for permanent installation

## MarineFlex YZp 0,6/1 kV

Article number: 16090

21-10-2019

### Construction characteristics

Certified for shipboard application	Yes
Standardization	IEC 60092-350/-360/-353
Number of cores	1
Nominal cross section conductor	35 mm <sup>2</sup>
Conductor material	Copper
Conductor surface	Bare
Standardization conductor material	IEC 60228
Shape of conductor	Round
Conductor category	Class 5 = flexible
Core insulation	XLPE (VPE)
Core identification	Colours and numbers
Conductor coding in accordance with HD 308 S2	Yes
Core lay-up	Concentric layers
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound
Colour outer sheath	Black
Standardization sheath material	IEC 60092-360

### Properties

Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1/2
Low smoke	IEC 61034-2
Nominal outer sheath thickness	1.2 mm
Outer diameter approx.	11.9 mm



Power cable  $\geq 1$  kV, for permanent installation

## MarineFlex YZp 0,6/1 kV

Article number: 16090

21-10-2019

### Technical characteristics

Tensile load	525 N
Min. bending radius during installation	83 mm
Min. permitted bending radius, stationary application/permanent installation	48 mm
Permitted cable outer temperature, in movement	-20 / 70 °C
Permitted cable outer temperature, fixed	-40 / 70 °C
Max. conductor temperature	90 °C

### Electrical characteristics

Nominal voltage U <sub>0</sub>	0.6 kV
Nominal voltage U	1 kV
Test voltage	3500 kV
Conductor DC resistance @ 20°C	0.554 Ohm/km
Conductor AC resistance @ max. cont. Conductor temp.	0.7064054 Ohm/km
Inductance	0.211 mH/km